

**#1 WATERPROOFING SOLUTION PROVEN!**

fast & easy to apply

suited to all types of buildings

substantially prolongs roof lifespan

safe & eco-friendly

affordable & cost-effective

sun & UV resistant

use on horizontal, vertical & inclined surfaces

protects & restores



**Gurtex**<sup>®</sup>

**WATERPROOF ANTI-CORROSION BARRIERS**





### **TOUGH & LONG LASTING**

Gurtex® substantially extends the lifespan of concrete, wood, corrugated iron or tiled roofs and structures. The product is not self-flammable nor does it burn.



### **FAST & EASY TO APPLY**

The product can be applied with minimal preparation to substrate.



### **SAFE & ECO-FRIENDLY**

The water-based latex barrier is odourless and does not leach harmful chemicals or gases into the soil, water or air.

# PROTECT IT

Gurtex® protects by waterproofing and smoothing surfaces while sealing against corrosion. Gurtex can stop leaks caused by material deformation, heat expansion, cracking, piercing (due to the installation of roof fixtures), loose joint mountings and rust.

Gurtex Products is suited to all types of buildings and structures and can be applied to a wide variety of materials including metals, galvanized materials, PVC piping, fibreglass, cement, tiles and paint. Use on:

- Corrugated iron, tiled or wooden roofs
- Horizontal concrete roofs, decks and patios
- Concrete infrastructure like pipelines, tunnels, dams and culverts
- Cellar floors and walls
- Artificial pools and fish ponds

## GURTEX® SG - 338

### Spray-on waterproof membrane (Exterior)

Gurtex SG-338 for professional waterproofing combines two chemical compounds using a twin-nozzle specialist sprayer. It provides full **waterproofing** and **anti-corrosion** coverage to large surfaces that have irregular shapes.

- Does not deteriorate in full sun or under water.
- Stretches up to 10 times its size without tearing.
- Apply to horizontal, vertical and sloped surfaces.
- Apply to damp and damaged surfaces.
- Does not need to be cut to size – no corner joins.



## GURTEX® SG - 368

### Brush, Roller or Airless Spray (Exterior)

Gurtex SG-368 is a single component, **black** high-viscosity paste for application with a paintbrush, roller or 220 bar airless sprayer. Provides **waterproofing** and **anti-corrosion** protection on a wide range of exterior surfaces including wooden, concrete or tiled roofs. It is easy to apply around water inlets and outlets, guttering, overlapping edges, fasteners, fixtures and taps.



## GURTEX® SG - 378

### Brush, Roller or Airless Spray (Interior)

Gurtex SG 378 is a single component, **white** high viscosity paste for application with a brush, roller or 220 bar airless spray. Superb **waterproofing** and **anti-corrosion** protection for basement and interior ceilings, walls, floors and fixtures across a range of building materials. Can be tinted. The surface cures within 40 minutes.



## GURTEX® SG - 168

### Brush, Roller or Airless Spray (Exterior)

Gurtex SG-168 is a single component, **white** high-viscosity paste for application with a paintbrush, roller or 220 bar airless spray.

Provides **heat-insulation, waterproofing** and **anti-corrosion** protection. Proven to reduce roof temperature by 12 to 14 degrees.

Gurtex SG-168 is an energy-saving waterproofing solution for corrugated iron, tiled or wooden roofs. It improves indoor thermal comfort without expensive air-conditioning.

Superb sealing with high bonding strength and crack sealing capability.





# RESTORE IT

The Gurtex® anti-corrosion waterproofing range is imported and distributed by approved agents in Africa, Asia-Pacific, Australia, Mauritius and the Caribbean Islands.



[www.gurtexwaterproofing.com](http://www.gurtexwaterproofing.com)  
[sales@gurtexwaterproofing.com](mailto:sales@gurtexwaterproofing.com)

